

Economic and Technological Feasibility Analysis of Biogas Production from Biomass Wastes by Adding Hydro char and Hydrothermal Pretreatment

KwangHun Cha¹, UnChol Ri², GyongBong Ju², YongBae Kim², ChangIl Ri², TongHo Kim¹, YongHwan Kim²

¹Institute of Development Strategy of Science and Technology, State Academy of Sciences, Pyongyang, Democratic People's Republic of Korea

²Department of Natural Energy Engineering, Hamhung University of Hydraulics and Power, Hamhung, Democratic People's Republic of Korea

> ^{*}Corresponding author Email address : riunchol927@126.com ³Research Scholar, J.P. University, Chapra, Bihar, India

> > Email:- sarvesh101278@gmail.com

Highlights

- BHC by bamboo reside (substrate: distilled water = 1:10) at 200°C led to the highest biogas yield.
- 75FPW+25LF enhanced the biogas yield compared to the control 100LF at 220°C.
- HTP of TR at 140°C and rice straw at 160°C led to the highest biogas and CH4 yield.
- The investment recovery duration reduced 163 days with the 1 000 m3 biogas plants.

ABSTRACT

Anaerobic digestion is an effective method of treating animal wastes and biomass Article Info wastes, reducing pollution by them and producing regenerative energy in the form Publication Issue of methane (methane gas). As renewable bioenergy resources, fish processing Volume 10, Issue 1 wastes, tofu residue and lignocellulose biomass (bamboo residue and rice straw) are identified as cheap and have a wide range of sources, so they can be used as an January-February-2023 effective substrate for biogas production. When fish processing waste with additive Page Number Hydro char (200°C and 220°C), hydrothermal pretreated tofu residue (140°C) and 356-365 lignocellulose biomass (rice straw: 160°C) are subjected to anaerobic co-digestion, biogas production can be increased. In addition, when liquid fraction from hydrothermal carbonization (200°C-280°C) and fish processing wastes are mixed in Article History Accepted: 15 Jan 2023 a certain ratio and used as raw materials for anaerobic digestion to carry out Published: 05 Feb 2023 anaerobic co-digestion, optimal output of biogas can be produced. This paper aims at the technology of producing biogas and maximizing the production by anaerobic digestion of fish processing wastes and tofu residue with Hydro char obtained from bamboo residue at a certain temperature (200°C) according to hydrothermal

Copyright: © the author(s), publisher and licensee Technoscience Academy. This is an open-access article distributed under the terms of the Creative Commons Attribution Non-Commercial License, which permits unrestricted non-commercial use, distribution, and reproduction in any medium, provided the original work is properly cited



carbonization, and making an economic and technological analysis of production process. Through a Break-even point analysis, producing biogas using hydrothermal Pre-treatment and adding Hydro char has more advantages than the without Pre-treatment method in both production volume and investment recovery duration. It was demonstrated that the comparison and evaluation of without Pre-treatment and adding Hydro char, hydrothermal Pre-treatment approach, the investment recovery duration could be reduced from 419 days to 256 days with the large-scale biogas plants of 1 000 m³ as a criterion.

Keywords: Hydro char, Hydrothermal Pre-treatment, Food Processing Waste, Biogas, Break- even Analysis

I. INTRODUCTION

Many serious problems such as environmental pollution and depletion of fossil fuels are being posed with continuous changes and developments of human civilization and economy. In particular, the shortage and depletion of fossil fuels (coal, oil and natural gas, etc.) is emerging as one of the important issues to be urgently solved around the world. Therefore, many countries are focusing on the development of ecofriendly and sustainable new energy.

In 2016, the total output of fish in China was 49.2 million tons, accounting for approximately 62% of the world's total fish output [5]. Fish processing wastes generated in the process of fish treatment account for more than 10% of the fish weight, which means that in 2016, the annual output of fish processing wastes in China was 4.9 million tons [15]. Traditionally, fish processing wastes are disposed by burying down the earth or burning into fire, but these methods cause problems of groundwater pollution, greenhouse gas or even toxic gas emissions, occupying potentially arable land, and spending much money.

Next, tofu residue (TR) is a byproduct of tofu production or soybean beverage manufacturing. Generally, every 1 000 L of soymilk produces about 250 kg of tofu residue [11]. It is estimated that approximately 14 million tons of tofu residue is generated all over the world each year, bringing environmental burden.

In addition, rice straw is one of the most abundant lignin fiber crop wastes in China. This lignocellulose biomass is not biodegraded easily and has a complex structure [8-10]. The co-digestion by lignocellulose biomass pretreated hydrothermally is very useful in improving the effectiveness of biogas production. Hydrothermal Pre-treatment becomes an interesting technique for the Pre-treatment of lignocellulose material [12, 13]. Hydrothermal Pre-treatment technology has considerable advantages of being very effective, eco-friendly with low energy requirements, and reducing emissions of toxic substances. [3, 4, 14, 15]

This study focuses on three subjects; (1) the codigestion of Hydro char produced by bamboo residues, fish processing wastes and liquid fraction of hydrothermal carbonization; (2) a method of producing biogas with tofu residue and rice straw pretreated hydrothermally; (3) economic and technological analysis of maximizing methane yield and net energy output from methane.

II. Technological Principle of Biogas Production Process by Hydrothermal Carbonization

The detailed principle of the process for manufacturing biogas is shown in Figure 1. [4]



Figure 1. Technological principle diagram of biogas production process by hydrothermal carbonization and hydrothermal Pre-treatment

Material 1: bamboo residue (substrate: distilled water=1:10); additive (1): dilute hydrochloric acid; ferrites.

Material 2: tofu residue; rice straw; additive (2): Hydro char; liquid fraction of hydrothermal carbonization (LFHTC).

First, as shown in Figure 1, hydrothermal carbonization is carried out at a certain hydrothermal carbonization temperature (200°C) for hydrothermal reaction time of 1 hour to obtain bamboo Hydro char, using bamboo reside (substrate: distilled water=1:10) as raw materials. Optimal reaction conditions are ensured during this hydrothermal carbonization process, and diluted hydrochloric acid and iron oxide are added as additives. [16]

The reaction temperature conditions and additive parameters are shown in detail in Table 1 and Table 2 below. **Table 1.** Parameters for hydrothermal carbonizationreaction conditions.

Reaction condition	Paramet	Unit	
Reaction condition	er		
Mixing ratio of water and	1.10		
bamboo residue	1.10	-	
Temperature	200	°C	
Pressure	15	bar	
Heating rate	3	°C/min	

Table 2. Additive parameters of hydrothermalcarbonization.

Additive	Parameter	Unit
Dilute	10	m1/I
hydrochloric acid	10	ШЦ/ Ц
Ferrites	3	g/L

Second, the obtained Hydro char is separated into solid Hydro char and liquid fraction of hydrothermal carbonization [3, 4]. Additives are mixed with separated solid Hydro char, and liquid fraction of hydrothermal carbonization is used as the raw material to carry out anaerobic co-digestion.

Third, tofu residue and rice straw is pretreated in the optimal hydrothermal Pre-treatment conditions (tofu residue; 140°C [3], rice straw; 160°C), and anaerobic co-digestion is carried out with Hydro char (mixing ratio 2:1 [4]) and liquid fraction of hydrothermal carbonization (mixing ratio 25%:75% [3]) to produce biogas.

III.The Technological Parameters for Manufacturing Biogas

Tables 3 and 4 below show the technological parameters of the biogas production by hydrothermal carbonization and hydrothermal Pre-treatment by processes.

Additive	Parameter	Unit
Hydro char	4	g/L
Liquid fraction of		
hydrothermal	25, 75	0/-
carbonization and Material	23+73	90
2		

Table 3. Additive parameters of anaerobic digestionand co-digestion.

Table 4. Parameters of hydrothermal Pre-treatment.

	Dro trootmont	Pre-	
Material	tomporature (°C)	treatment	
	temperature (C)	time (min)	
Tofu residue	140	30	
Rice straw	160	30	

4. Biogas Production Process

4.1. Raw Material Processing

Fish processing wastes: After removing bones, thorns and scales from the mixture containing fish intestines, fat, swim bladder, bones, fins, and scales from the fish processing, the mixture is cut into the size of 3-5 mm by using a grinder. [4]

Bamboo residue: After cutting bamboos, they are allowed to leave to dry overnight at 60°C. When moisture in the chopped samples is less than 3%, they are pulverized into small particles by a turbine grinder and passed through a 60-mesh screen. The prepared bamboo powder has an average particle size of 250-300 μ m and is used as feedstock for hydrothermal carbonization. [4]

Tofu residue: The tofu residue is pulverized with a blender and then mixed evenly to be used as feedstock for anaerobic digestion. [2]

Lignocellulose biomass (rice straw): The rice straw is first dried in the air to contain moisture of less than 10%, then subsequently cut into the size of 425 μ m and stored in plastic bags at room temperature until further use. [8]

Inoculum: The inoculum is collected from the bottom settlement of anaerobic fermentation tank

that was fed with food and kitchen wastes.

4.2. Production of Hydro char

After bamboo residue is dried at 60°C overnight, dry bamboo powder is mixed with deionized water in a ratio of 1:10 [17] and transferred into a cylindrical stainless steel reactor. The experimental conditions are set at 200°C, a heating rate of 3°C/min and a reaction time of 1 hour. The content is continuously stirred at 90 rpm, and when the hydrothermal carbonization is finished, the content temperature is cooled down to room temperature and the gaseous product is then released via the gas valve. The liquid product is separated by vacuum filtration with 0.45 µm pore-size cellulose filter paper. The residue is the bamboo Hydro char and is dried overnight in an oven at 105°C. The dried Hydro char is stored in a plastic bag and later used as an additive in anaerobic digestion. [4]

4.3. Hydrothermal Pre-treatment of Tofu Residue and Rice Straw

Cooperative anaerobic fermentation is carried out using the tofu residue and rice straw pretreated with hydrothermal Pre-treatment at different temperatures between 130°C and 180°C as substrates. The pretreatment method for hydrothermal carbonization of tofu residue and rice straw is as follows. Mix the substrate and deionized water in a ratio of 1:1 and mix evenly. The mixed material is placed in a columnshaped high-temperature and high-pressure reactor (4848, Parr Instrument Company, USA), and a stirrer is installed. The conditions of the hydrothermal carbonization process are that the temperature range is between 130°C and 180°C [2], the heating rate is 3°C/min, and the reaction time is 1 hour at the required temperature. The reaction temperature is controlled with a thermostat (4848 Parr Instrument Company, USA). The reaction contents are continuously stirred at 90 rpm, and the stirring speed is controlled by a speed the end of the hydrothermal controller. At carbonization reaction, the heater is turned off and the



reactor is cooled to room temperature. It takes about 4-5 h to cool the reactor down to room temperature of 25°C, and the pressure is reduced from 8-12 bar to 3-4 bar. After the temperature is lowered to 25°C, turn on the gas valve to remove gas products, and separate liquid products with a vacuum pompom using 0.45 μ m-sized cellulose filter paper. The filtered tofu residue and the hydrothermal liquid of rice straw are stored at -20°C and used as raw materials for anaerobic fermentation.

4.4. Anaerobic Decomposition and Cooperative Fermentation

An anaerobic reaction is performed by putting the substrate and inoculum in the reaction tank. Add diluted hydrochloric acid to the gas collection tank to set the pH 3 or less to prevent the decomposition of CO₂. [9]

Argon gas was introduced into the reactor for 5 min to ensure anaerobic conditions. The reactor was then incubated in a constant-temperature water bath (DK-S28, Shanghai Jinghong) (Figure 2). The temperature of the water bath is controlled at $37 \pm 1^{\circ}$ C in mesophilic anaerobic fermentation. [6]

Figure 3 below shows the biogas production process diagram by hydrothermal carbonization and hydrothermal Pre-treatment. [2-4]



Figure 2. Schematic diagram of batch anaerobic digestion system



Figure 3. Biogas production process diagram by hydrothermal carbonization and hydrothermal Pre-treatment.

IV. Economic and Technological Analysis of Biogas Production Process

5.1. Technological Analysis of Biogas Production Process

- Since Hydro char is used as a carrier for anaerobic fermentation microorganisms, it is possible to increase the biogas productivity using anaerobic fermentation microorganisms by ensuring a habitat for the growth and proliferation of methane gas-generating microorganisms during anaerobic fermentation.
- 2) The effectiveness of anaerobic fermentation can be increased by allowing the anaerobic decomposition of raw materials for fermentation to proceed well because substances that are biologically difficult to decompose are converted into substances with low molecular weight through hydrothermal Pre-treatment.
- 3) Since Hydro char is used as an additive, when biomaterials with high nitrogen content are used as raw materials for anaerobic fermentation, the effectiveness of anaerobic fermentation can be increased by rationally controlling the carbon/nitrogen ratio of the fermentation substrate.
- 4) Since a biological material with high moisture content is used as the raw material for hydrothermal carbonization, the drying process is not required in the preparation of the fermentation raw materials, so the energy required for drying the biological material can be saved.



5) Since the hydrothermal liquid generated in the hydrothermal carbonization process can be used as an anaerobic fermentation raw material, there is an eco-friendly advantage in that it prevents secondary pollution that may occur in the hydrothermal carbonization process and converts hydrothermal liquid waste into biomass energy.

There is a significant difference in methane yields when raw materials without hydrothermal Pretreatment are used as they are and when raw materials subjected to hydrothermal Pre-treatment are used.

Fish processing waste

The maximum methane yields was 219 mL/g-VS when a mixture of fish processing wastes and hydrothermal liquid was used, and the methane yields increased by 64% compared to when only fish

processing wastes were used. At this time, the highest pure methane energy production is 3 410 kJ/kg-VS. [3, 4]

Tofu residue

The maximum methane yields is 200.1 mL CH₄/g-VS when tofu residue with hydrothermal Pre-treatment is used, which indicates that its methane yields is 34% higher than when tofu residue without hydrothermal Pre-treatment is used. [2]

Rice straw

The highest methane production yields of rice straw added 5% NaOH was 132.7 mL/g VS, which the hydrothermal Pre-treatment was given for 10 min at 200°C. [1]

Table 5 shows the changes in methane yields by hydrothermal Pre-treatment and without Pretreatment of several substrates during anaerobic digestion.

Substrate		Methane yields (mL/g-VS)	Increment rate (%)
Method 1	Fish processing waste	97.0	
(Hydrothermal Pre-	Tofu residue	150.6	
treatment is not		07	
undergone)	Kaw straw	97	
Method 2	Fish processing waste	219.0	125.8
(Hydrothermal Pre-	Tofu residue	207.0	37.5
treatment is undergone)	Raw straw	132.7	36.8

5.2. Economic Analysis

The analysis of capital investment in year:

Equation 1 below shows the model of calculating gross investment in biogas production when using two different methods. Fixed costs and variable costs required for biogas production are shown in Equation 2 and 3 where

$$C_t = C_e + C_r \tag{1}$$

$$C_{e} = C_{ep} + C_{em} + C_{en} + C_{ec}$$
(2)

$$C_{\rm r} = C_{\rm rh} + C_{\rm ri} + C_{\rm rj} \tag{3}$$

 C_t : gross investment; C_e : fixed costs; C_r : variable costs; C_{ep} : costs of hydrolysis precipitation equipment for Pre-treatment processes of raw materials; C_{em} : methane gas production equipment costs; C_{en} : costs of



equipment for treating methane fermentation liquid and fermentation waste; C_{ec} : costs of methane gas trapping equipment; C_{rh} : labour costs; C_{ri} : power rates; C_{rj} : raw materials purchase costs.

(1) Fixed costs

According to research data, the costs of relevant equipment have been identified on the basis of methane gas production equipment of 1 000 m³.

				cost unit: 10 00	0 RMB
	Equipment cost				
Cost	Before-treatment	Gas	Fermentation	Gas	
Production method	equipment of raw	production	waste treating	trapping	Total
	materials	equipment	equipment	equipment	
Method 1	3	2 500	15	2	2
Withou I	5	2 300	1.5	2	506.5
Method 2	30	2 500	15	2	2
	50	2 300	1.5	2	533.5

Table	6. Fixed	l costs.
-------	-----------------	----------

Method 1 in the table above is a general mode of biogas production where the hydrothermal Pre-treatment of raw materials is not undergone whereas Method 2 is a mode of biogas production where the hydrothermal Pre-treatment of raw materials is undergone. Here, there is a certain gap in their costs because Pre-treatment of raw materials is undergone in Method 2.

Investment in biogas production processes is 25 065 000 RMB in Method 1, and 25 335 000 RMB in Method 2.

(1) Yearly variable costs

Variable costs include labor costs and raw materials purchase costs. According to investigation, the number of working staff is 160 among whom 140 are field workers and 20 are management staff. Hydrothermal Pre-treatment process requires 10 more labour staff. Monthly salary of field workers are 2 500 RMB, which is the average salary amount in the city, and that of management staff is 4 000 RMB.

As power rates equal to 0.5 RMB/kWh, daily power consumption is 1 250 kW, and daily raw material treatment amount is 100 tons.

						cost unit: 10	000 RMB
	Cost	Operation cost					
Production method	COSL -	Labour cost	Dorrow		Raw materials		
		Number of field	Management	rates	Raw	Transportation	Total
	\searrow	workers	staff		materials cost	cost	
Method 1		420.000	96.000	22.8125	91.2500	109.5000	739.5625
Method 2		450.000	96.000	23.7250	91.2500	109.5000	770.4750

Table 7.	Operation	costs	in	year.
----------	-----------	-------	----	-------

5.3. Profitability Analysis

In this paper, we did a Break-even point analysis of traditional method of treating biomass wastes and hydrothermal Pre-treatment method, and based on



this, we compared and evaluated the profitability of each method.

(1) Break-even point analysis

Break-even point is equal to fixed costs divided by the retail price per unit, minus the variable costs per unit. [7]

$$BEP = FC/((p - vc))$$
(4)

Where: BEP - production volume in Break-even point, FC - fixed costs, p - price, vc - variable cost per unit.

Break-even point analysis is one of the useful tools for researching into the relationship between fixed costs, variable costs and revenue. Break-even point determines the point when an investment generates positive revenue.

Break-even point analysis helps to calculate the production volume at a given cost necessary for making up all the costs. It also helps to figure out the proper price which can compensate for all the costs at a given level of production volume.

(2) Break-even point analysis of two methods Regarding daily production volume, the production volume of Method 1 is 20 000m³ and Method 2 is 30 000m³, which means the yearly production volume of Method 1 equals to 7 300 000 m³/year, and that of Method 2 amounts to 10 950 000 m³/year.

Operation cost in Method 1 in year is 7 395 625 RMB/year, and 7 704 750 RMB/year in Method 2. Therefore, the variable cost per unit in Method 1 is – 1.013 RMB/m³, and 0.703 RMB/m³ in Method 2.

The price of biogas is 4 RMB/m³.

Production volume required to reach Break-even point (BEP)

$$BEP_1 = \frac{FC}{p - vc} = \frac{25\ 065\ 000}{4 - 1.013} = \frac{25\ 065\ 000}{2.987}$$
$$= 8\ 391\ 362.57$$

$$BEP_2 = \frac{FC}{p - vc} = \frac{25335000}{4 - 0.703} = \frac{25335000}{3.297}$$
$$= 7684258.41$$

BEP₁: Production volume at BEP in Method 1 BEP₂: Production volume at BEP in Method 2

As shown Figure 4, It was demonstrated that the Break-even point after producing 8 391 362.57 m³ of biogas, and investment recovery duration required is 419 days in Method 1. Meanwhile, in Method 2, it was calculated that the Break-even point after producing 7 684 258.41 m³ of biogas, and the investment recovery duration required is 256 days. As above mentioned in Break-even point analysis, producing biogas using hydrothermal Pre-treatment of biomass wastes has more advantages than the previous traditional method in both production volume and investment recovery duration.





V. Conclusion

Traditionally, food processing wastes have been treated by burial or burning, but this method is expensive and poses environmental problems. Burying in the ground occupies a lot of land resources, and after burial, it pollutes leaching groundwater, and the method of burning has a defect in releasing global warming gas and toxic gas. This study investigated the effect of Hydro char made from bamboo residue on the anaerobic



fermentation of fish and tofu residue. Then, researches were made on the effect of the addition bamboo Hvdro char on the anaerobic of fermentation of fish processing wastes, the cooperative fermentation characteristics and optimal mixing ratio between fish processing wastes and hydrothermal carbonization liquid, and the optimal hydrothermal Pre-treatment temperature of tofu residue and rice straw. Furthermore, this study delved into the mixing ratio and mixed fermentation characteristics of the fermentation liquid of tofu residue and rice straw according to the optimal temperature of hydrothermal Pre-treatment. Next, it was discovered that when fermentation raw materials are used that have undergone Hydro char addition and hydrothermal Pre-treatment, biogas production, methane production, methane content in biogas, and pure energy gain are maximized, and the inhibition of anaerobic fermentation due to ammonia nitrogen by the addition of hydrothermal carbon is eliminated. In this research, as a result of doing Break-even point analysis, comparison and evaluation of traditional fish processing wastes treating method and hydrothermal Pre-treatment approach, investment recovery duration could be reduced from 419 days to 256 days using Method 2 with the large-scale biogas plants of 1 000 m³ as a criterion. Finally, the research revealed that when producing biogas from food processing wastes using hydrothermal carbonization and hydrothermal Pretreatment, biogas production volume could be increased in comparison to the traditional way of not using Pre-treatment approach, and investment recovery duration could be reduced to 163 days.

Acknowledgements

This study was supported by the National Key R&D Program of DPR of Korea (Grant No. 2022RKR927329522) and the Program of Introducing Talents (Grant No. RGC1983117). The authors would like to thank Prof. RI, Hamhung University of Hydraulics and Power, who gave us much valuable advice in the early stages of this work. We also appreciate the editor and anonymous reviewers for their helpful comments.

Disclosure statement

The authors report there are no competing interests to declare

ORCID

UnChol Ri http://orcid.org/0000-0002-4474-3389

VI. REFERENCES

- Chandra R., Takeuchi H., Hasegawa T., 2012. Hydrothermal Pre-treatment of rice straw biomass: A potential and promising method for enhanced methane production. Applied Energy, 94, 129–140.
- [2]. Choe U., Ahmed M. M., Zhang X, Sheng K, Zhou X, Wang K., 2021. Effects of hydrothermal Pre-treatment and bamboo Hydro char addition on anaerobic digestion of tofu residue for biogas production. Bioresour Technol. 336, 125297.
- [3]. Choe, U., Mustafa, A. M., Lin, H., Choe, U., Sheng, K., 2020. Anaerobic co-digestion of fish processing waste with a liquid fraction of hydrothermal carbonization of bamboo residue. Bioresour Technol. 297, 122542.
- [4]. Choe, U., Mustafa, A. M., Lin, H., Xu, J., Sheng, K., 2019. Effect of bamboo Hydro char on anaerobic digestion of fish processing waste for biogas production. Bioresour. Technol. 283, 340–349.
- [5]. FAO, 2018. FAO yearbook: Fishery and Aquaculture Statistics. 2016. FAO, Rome, 104.
- [6]. Kafle, G. K., Kim, S. H., 2013. Anaerobic treatment of apple waste with swine manure for biogas production: Batch and continuous operation. Appl. Energy. 103, 61–72.
- [7]. Kampf R., Majerčák P., Švagr P., 2016.Application of Break-even point Analysis



Primjena Break-even point analize. Naše more. 63 (3), 126-128.

- [8]. Mustafa, A. M., Li, H., Radwan, A. A., Sheng, K., Chen, X., 2018. Effect of hydrothermal and Ca(OH)2 Pre-treatments on anaerobic digestion of sugarcane bagasse for biogas production. Bioresour. Technol. 259, 54–60.
- [9]. Mustafa, A. M., Poulsen, T. G., Sheng, K., 2016. Fungal Pre-treatment of rice straw with Pleurotus ostreatus and Trichoderma reesei to enhance methane production under solid-state anaerobic digestion. Appl. Energy. 180, 661– 671.
- [10]. Mustafa, A. M., Poulsen, T. G., Xia, Y., Sheng, K., 2017. Combinations of fungal and milling Pre-treatments for enhancing rice straw biogas production during solid-state anaerobic digestion. Bioresour. Technol. 224, 174–182.
- [11]. Nguyen, T. A., Ngo, H. H., Guo, W. S., Zhang, J., Liang, S., Tung, K. L., 2013. Feasibility of iron loaded 'okara' for biosorption of phosphorous in aqueous solutions. Bioresour Technol. 150, 42– 49.
- [12]. Reza, M. T., Becker, W., Sachsenheimer, K., Mumme, J., 2014. Hydrothermal carbonization (HTC): near infrared spectroscopy and partial least-squares regression for determination of selective components in HTC solid and liquid products derived from maize silage. Bioresour. Technol. 161, 91–101.
- [13]. Reza, M. T., Rottler, E., Tölle, R., Werner, M., Ramm, P., Mumme, J., 2015. Production, characterization, and biogas application of magnetic Hydro char from cellulose. Bioresour. Technol. 186, 34–43.
- [14]. Xia, A., Cheng, J., Murphy, J. D., 2016. Innovation in biological production and upgrading of methane and hydrogen for use as gaseous transport biofuel. Biotechnol. Adv. 34 (5), 451–472.
- [15]. Xu, J., Mustafa, A. M., Sheng, K., 2016. Effects of inoculum to substrate and co-digestion with bagasse on biogas production of fish waste. Environmental Technology, 1–27.

- [16]. Yan, W., Perez, S., Sheng, K., 2017. Upgrading fuel quality of moso bamboo via low temperature thermochemical treatments: dry torrefaction and hydrothermal carbonization. Fuel. 196, 473–480.
- [17]. Zhang, J., Lü, F., Luo, C., Shao, L., He, P., 2014. Humificatcicon characterization of biochar and its potential as a composting amendment. J. Environ. Sci. 26 (2), 390–397.

Cite this article as :

KwangHun Cha, UnChol Ri, GyongBong Ju, YongBae Kim, ChangIl Ri, TongHo Kim, YongHwan Kim, "Economic and Technological Feasibility Analysis of Biogas Production from Biomass Wastes by Adding char and Hydrothermal Pre-treatment", Hydro International Journal of Scientific Research in Science and Technology (IJSRST), Online ISSN: 2395-602X, Print ISSN : 2395-6011, Volume 10 Issue 1, pp. 356-365, January-February 2023. Available at doi • https://doi.org/10.32628/IJSRST2310144 Journal URL : https://ijsrst.com/IJSRST2310144