

## Free Convective MHD Flow Through Porous Medium

Sarvesh Kumar Department of Mathematics, Ganna Utpadak(P.G.) College, Baheri -243201, Bareilly (U.P.), India

**ABSTRACT-** In the present paper, the effect of equilibrium temperature gradient and magnetic field on the rate of heat transfer, velocity and temperature has been studied. Numerical calculations for the rate of heat transfer, velocity and temperature are obtained and shown graphically. The highly porous medium which is bounded by an infinite vertical non-conducting plane surface has been considered and two dimensional free convective MHD flow of a stratified viscous fluid has discussed.

Keywords : Free convective effect, MHD flow, Viscous fluid, Magnetic field, porous, medium.

**INTRODUCTION** - The unsteady and steady transmission of a homogeneous viscous fluid by means of a porous medium and is surrounded by a vertical plate with varying constant temperature has studied by 'Raptis et al.' and 'Raptis'. 'Sharma' suggested the flow for free convective effect with ordinary viscous fluid to infinite vertical porous plate having constant suction and heat flux. 'Achary et al.' investigated the impact of magnetic field effection on the mass transfer flow for free convection through porous medium having constant suction and heat. 'Noushima et al.' investigated unsteady free convective MHD flow for walter's memory with constant suction and heat sink. 'Magyari et al.' studied the analytical study for unsteady free convection for porous media. 'Soundalgekhar' studied the various aspect for horizontal magnetic field and variable suction on the free convection flow with vertical porous plate and denoted the different parameters and flow of mercury and ionized air. 'Turchuk and Shildovskil' studied the equations of motion for the fluid having viscous micro layers, its relation with viscosity, thermal conductivity and diffusion, deviation of field variable from hydrostatic value and the effect of equilibrium stratification through porous medium was studied by 'Mondal and chaudhary'.

The present paper is the study of unsteady free convective MHD flow in two dimensional stratified viscous conducting fluid through highly porous medium having infinite vertical non-conducting plane under the effect of a homogenous transverse magnetic field. It has seen that the temperature of the surface, which have oscillating behaviour with respect to the time varies vertically. The energy transport is effected by force distributed is due to density variation for convection for free flow. The flow in a especially porous medium is the main aspect for the study due to many application in industrial problem such as petroleum, nuclear and chemical industries. The magnetic effects are extremely used in the power generation.

1. FORMULATION AND SOLUTION OF THE PROBLEM : Unsteady two dimensional flow of viscous conducting and thermally stratified fluid by highly porous medium surrounded by an unlimited non-conducting vertical plane, which is moving vertically having a constant velocity V has considered. We

IJSRSET2310299 | Received : May 10, 2019 | Accepted : June 15, 2019 | May-June-2019 [ 6 (3) : 487-494 ]

have also consider the x'-axis, which is vertically upward along with the plane, y'-axis is normal to the plane B<sub>0</sub> (= q<sub>0</sub>H<sub>0</sub>) shows uniform magnetic field strength, this value represent the normal action of the plane. The relationship between the temperature and pressure of a fluid have the following interrelationship  $\theta'=\theta_e + T'$ ,  $\sigma' = \sigma_e - \alpha\sigma_0 T'$  and  $p' = p_e + \bar{p}$ . The temperature  $\theta_e$  at equilibrium, density  $\sigma_e$  and pressure  $p_e$  have the following relationship  $\theta_e = \theta_0 + A'_F x'$ ,  $\sigma_e = \sigma_0(1 - \alpha\theta_0)$  and  $\frac{dp_e}{dx'} = -\sigma_e g$ . Where T' and p indicates the temperature deviation and pressure deviation respectively, equilibrium temperature gradient for fluid is  $A'_{\theta}$ , the density is represented by  $\sigma_0$ , where  $\theta_0$  represents the temperature, coefficient of volume expansion is denoted by  $\alpha$ , where g is acceleration due to gravity.

The plate temperature is considered as follows :

$$\theta'_{\omega} = \theta_{\rm e} + \theta_{\rm w} (1 + \epsilon e^{i\omega't'}),$$

in the above equation  $\theta_w > 0$ , the time is indicated by t', which is constant, the frequency of oscillation is  $\omega'$ , where as  $\in (< 1)$  is a constant value.

Concerning T',  $\bar{p}$  and the components of velocity, these are independent of x'. Equation of momentum and energy neglecting viscous dissipation can be represented as

$$\frac{\partial q'}{\partial t'} = \alpha g T' - \frac{\mu}{\kappa'} q' + \mu \frac{\partial^2 q'}{\partial {y'}^2} - \frac{\rho}{\sigma} B_0^2 q', \qquad (2.1)$$

and 
$$\frac{\partial T'}{\partial t'} = -A'_{\theta}q' + \frac{K}{\sigma_0 C_p} \frac{\partial^2 T'}{\partial {y'}^2} + \frac{\rho}{\sigma} B_0^2 {q'}^2, \qquad (2.2)$$

where q' represents the velocity components along x'-axis, k denotes the thermal conductivity,  $C_P$  represents the specific heat at constant pressure, K' represents the permeability of the medium and  $\mu$  denotes the kinematic coefficient of viscosity.

Now we consider the non –dimensional variables as follows :

$$y = \frac{y'V}{\mu}$$
,  $q = \frac{q'}{V}$ ,  $T = \frac{T'}{\theta_w}$ ,  $\omega = \frac{\mu\omega'}{V^2}$  and  $t = \frac{t'V^2}{\mu}$ .

The above concern equations can be represented as

$$\frac{\partial^2 q}{\partial y^2} - \frac{\partial q}{\partial t} - mq = -GT, \qquad (2.3)$$

$$\frac{\partial^2 T}{\partial y^2} - P_r \frac{\partial T}{\partial t} = A_\theta P_r q - EM P_r q^2, \qquad (2.4)$$

where Grashoff number  $= \frac{\alpha g \theta_w \mu}{V^3}$ , Prandtl number  $= \frac{\mu C_p \sigma_0}{k}$ , Permeability parameter  $= \frac{V^2 K'}{\mu^2}$ , Equilibrium temperature gradient parameter  $= \frac{\mu A'_{\theta}}{\theta_w V}$ , Hartmann number  $= \frac{\mu \rho B_0^2}{V^2 \sigma}$  and Eckert number  $= \frac{V^2}{\theta_{\omega}} \ll 1$  are denoted by G, Pr, K, A<sub>0</sub>, M and E respectively.

International Journal of Scientific Research in Science, Engineering and Technology (www.ijsrset.com)

488

The boundary conditions are considered as follows :

q=1, T=1+
$$\in e^{i\omega t}$$
 at y=0

$$q, T \rightarrow 0$$
 as  $y \rightarrow \infty$  (2.5)

In view of above boundary conditions (2.5) the solution of equations (2.3) and (2.4) takes the form

$$q = \sum_{r=0}^{\infty} \in^{r} q_{r}(y) e^{ir\omega t}$$
$$T = \sum_{r=0}^{\infty} \in^{r} T_{r}(y) e^{ir\omega t}$$
(2.6)

If we consider the non-harmonic terms and the first harmonic terms then substituting equations (2.6) in equations (2.3) and (2.4). We get the differential equations in  $(q_0, T_0)$  and  $(q_1, T_1)$ :

$$\frac{d^2 q_0}{dy^2} - mq_0 = -G T_0; \qquad \frac{d^2 T_0}{dy^2} = A_\theta P_r q_0$$
(2.7)

and

$$\frac{d^2 q_1}{dy^2} - (i\omega + m) \ q_1 = -GT_1; \ \frac{d^2 T_1}{dy^2} - i\omega P_r T_1 = A_{\theta} P_r q_1$$
(2.8)

In reduced boundary conditions, we can find another equation (2.9)

$$q_0 = 1, q_1 = 0, T_0 = 1, T_1 = 1, \qquad \text{at } y = 0$$
$$q_0, q_1, T_0, T_1 \to 0, \qquad \text{as } y \to \infty \qquad (2.9)$$

In view of above boundary conditions, the solution of equations can be obtained in the form of velocity, and temperature field as below :

Case – Ist

then

if 
$$A_{\theta} < \frac{m^2}{4P_r G}$$
,  
 $q = \sum_{r=0}^{\infty} \epsilon^r (A_r e^{-\alpha_r y} + B_r e^{-\beta_r y}) e^{ir\omega t}$ . (2.10)

$$T = -\frac{1}{G} \left[ \sum_{r=0}^{\infty} \epsilon^r \left\{ (\alpha_r^2 - i\omega r - m) A_r e^{-\alpha_r y} + (\beta_r^2 - i\omega r - m) B_r e^{-\beta_r y} \right\} e^{ir\omega t} ) \right].$$
(2.11)

 $Case - II^{nd}$ 

$$A_{\theta} > \frac{m^2}{4P_rG},$$

then 
$$q = e^{-m_1 y} (\operatorname{Cosm}_2 y + \operatorname{C} \operatorname{Sinm}_2 y) + \sum_{r=1}^{\infty} \in^r (A_r e^{-\alpha_r y} + B_r e^{-\beta_r y}) e^{ir\omega t}$$
. (2.12)

$$T = -\frac{e^{-m_2 y}}{G} [\{m_1^2 - m_2^2 - m - 2m_1 m_2 C\} Cosm_2 y + \{C(m_1^2 - m_2^2 - m) + 2m_1 m_2\} sin m_2 y] - \frac{1}{G} \sum_{r=1}^{\infty} \epsilon^r [(\alpha_r^2 - i\omega r - m) A_r e^{-\alpha_r y} + (\beta_r^2 - i\omega r - m) B_r e^{-\beta_r y}] e^{ir\omega t}$$
(2.13)

 $Case - III^{rd}$ 

If 
$$A_{\theta} = \frac{m^2}{4P_r G} = \overline{A}_{\theta}$$
 (Critical value),

then  $q = (1 + Fy) e^{-\sqrt{\frac{m}{2}}y} + \sum_{r=1}^{\infty} \epsilon^r [A_{r+1}e^{-\alpha_{r+1}y} + B_{r+1}e^{-\beta_{r+1}y}]e^{ir\omega t}.$  (2.14)

$$T = \frac{1}{G} \left[ \frac{\left(F\sqrt{8K} + y\right) + (1 + MK)}{2K} \right] e^{-\sqrt{\frac{1}{2}my}} - \frac{1}{G} \sum_{r=2}^{\infty} \epsilon^{r-1} \left[ \{\alpha_r^2 - i(r-1)\omega - m\} B_r e^{-\beta_r y} \right] e^{i(r-1)\omega t},$$
(2.15)

where

$$(\alpha_0, \beta_0) = \left[\frac{1}{2} \left\{ m \pm \sqrt{m^2 - 4P_r G A_\theta} \right\} \right]^{1/2},$$

$$\begin{split} (m_1, m_2) &= \left[\frac{(4P_r GA_{\theta} K^2 \pm 1)(1 + MK)}{4K}\right]^{1/2}, \\ (\alpha_1, \beta_1) &= \left[\frac{1}{2} \left\{ i\omega(1 + P_r) + m \pm \sqrt{m^2 - 4P_r GA_{\theta} - \omega^2(1 - P_r)^2 + 2i\omega m(1 - P_r)} \right\} \right]^{1/2}, \\ (\alpha_2, \beta_2) &= \left[\frac{1}{2} \left\{ i\omega(1 + P_r) + m \pm \sqrt{\frac{2i\omega}{M}(1 + MK)(1 - P_r) - \omega^2(1 - P_r)^2} \right\} \right]^{1/2}, \\ A_0 &= -\frac{\beta_0^2 + G - m}{\alpha_0^2 - \beta_0^2}, \qquad B_0 = \frac{(\alpha_0^2 + G - m)}{\alpha_0^2 - \beta_0^2}, \\ m &= \frac{1}{K} + M, \\ C &= \frac{1}{2m_1m_2} \left[ G + (m_1m_2)^2 - m_2^2 - m \right], \\ A_1 &= -B_1 = \frac{G}{\beta_1^2 - \alpha_1^2}, \end{split}$$

$$A_2 = -B_2 = \frac{G}{\beta_2^2 - \alpha_2^2}$$
 and  $F = \left(\frac{2KG - 1}{8K}\right)(1 + MK)^{1/2}$ .

The velocity field can be defined as

 $q(y,t) = q_0(y) + \epsilon q_r(y)\cos\omega t + \epsilon q_i \sin\omega t$ , here  $q_r$  and  $q_i$ , these are the real and imaginary parts of  $q_1$ . If  $\omega t = \pi/2$ , then the relation for transient velocity becomes

$$q_{\theta} = q_0(y) + \in q_i(y).$$

The indication for the transient velocity  $q_{\theta}$  for different values of K, G, M and  $A_{\theta}$  with  $P_r = 0.71$  and  $\in = 0.02$  are indicated in Fig. 1 and Fig. 2.

490 L



Fig. 1. Variable in distribution of transient velocity at  $\epsilon = 0.02$ ,  $P_r = 0.71$ , G = 4,  $\omega = 6$ , for M = 0 and M = 2. The critical values  $\overline{A}_{\theta}$  for K = 1 and K = 2 are corresponded to curves 2 and 5.

Heat transfer rate at the plane for  $\omega t = \pi/2$  in terms of Nusselt number  $N = -\left(\frac{d\theta}{dy}\right)_{y=0}$  are shown in table – I.

## Table –I

Heat transfer rate in terms of variation in Nusselt number N, for various numerical values of  $\omega$ , G, K and  $A_{\theta}(P_r = 0.71, \epsilon = 0.02)$ .

| ω   | G   | К | Α <sub>θ</sub> | N (M=0) | N (M=2) |
|-----|-----|---|----------------|---------|---------|
|     |     |   | 0.01           | - 0.146 | - 0.152 |
|     |     | 1 | 0.05           | 0.029   | 0.031   |
|     |     |   | 0.10           | 0.129   | 0.134   |
|     | 4 – |   |                |         |         |
|     |     |   | 0.01           | -0.106  | -0.112  |
|     |     | 2 | 0.05           | 0.077   | 0.086   |
|     |     |   | 0.10           | -0.192  | -0.198  |
| 5 — |     |   |                |         |         |
|     |     |   | 0.01           | -0.091  | -0.104  |
|     |     | 1 | 0.05           | 0.104   | 0.117   |
|     |     |   | 0.10           | 0.230   | 0.239   |
|     | 8 – |   |                |         |         |
|     |     |   | 0.01           | -0.043  | -0.048  |
|     |     | 2 | 0.05           | 0.163   | 0.172   |
|     |     |   | 0.10           | 0.291   | 0.301   |
|     |     |   | 0.01           | - 0.226 | - 0.232 |
|     |     | 1 | 0.05           | - 0.065 | - 0.073 |
|     |     |   | 0.10           | 0.045   | 0.049   |

|    | 4    |   |                      |                          |                          |
|----|------|---|----------------------|--------------------------|--------------------------|
|    | 1    | 2 | 0.01<br>0.05         | -0.185<br>0.008          | -0.192<br>-0.009         |
| 10 |      |   | 0.10                 | 0.106                    | 0.011                    |
|    | 8 —— | 1 | 0.01<br>0.05<br>0.10 | -0.172<br>0.031<br>0.143 | -0.179<br>0.038<br>0.151 |
|    |      | 2 | 0.01<br>0.05<br>0.10 | -0.117<br>0.082<br>0.210 | -0.119<br>0.088<br>0.217 |

2. **DISCUSSION**: It is obious by the figures 1 and 2 that there is very high relationship between equilibrium temperature gradient parameter ( $A_{\theta}$ ) and transient velocity ( $q_{\theta}$ ).



Fig.2. Distribution in transient velocity at  $\epsilon = 0.02$ ,  $P_r = 0.71$ , G = 8,  $\omega = 6$ , for M = 0 and M = 2. Curves 2 and 5 denoted the critical values  $\overline{A}_{\theta}$  for K = 1 and K = 2.

If we increase the equilibrium temperature gradient parameter  $(A_{\theta})$ , then the transient velocity  $(q_{\theta})$  decreases all the time. The fluid velocity relative to the plate at the first increases with the increasing from the plane and gains the maximum value within the fluid and decreases exponentially for conditions  $0 < A_{\theta} \leq \overline{A}_{\theta}$  ( $\overline{A}_{\theta} =$ critical value). If conditions are like as  $A_{\theta} > \overline{A}_{\theta}$ , the relative velocity decreases. If we increase the distance of plane and the fluid flow relative to the plane condition and this is opposite to the direction of the motion of the plane, in these situations the magnetic field decreases in all. Which shows that the magnetic field application is unfavourable to the direction of flow. If the medium of flow is non porous letting  $K \to \infty$  as well as  $\overline{A}_{\theta} = \frac{M^2}{4P_rG} < A_{\theta}$ .

Then the velocity of fluid is always less than that of the plane.

Grashoff number shows the free convection effect, for G > 0 respons the cooled surface formulation. When the G,K and  $\omega$  increases the velocity will also increase.

In table-I the Nusselt number N with reference to the heat transfer effect has explained, which shows that for small  $A_{\theta}$ , heat is transferred from the fluid to the plane, but there is reverse condition for higher  $A_{\theta}$ .

## REFERENCES

| 1. | Raptis, A., Perdikis and Tzivanidis, S. :  | "Free con | nvection flow through a porous<br>medium bounded by a vertical surface",<br>Jour. of Phys., D: Applied Phys., Vol. 14,<br>L99-L102(1981).   |
|----|--|-----------|---|
| 2. | Raptis, A.   | : '       | "Unsteady free convection flow through a<br>porous medium", Int. Jour. Engg. Sciences, Vol. 21,<br>pp. 345 (1983).  |
| 3. | Sharma, P.R.   | :         | "Free convection effects on the flow past<br>a porous medium bounded by a vertical infinite<br>surface with constant suction and constant heat<br>flux", Jour. Phys. D. Appl. Phys. England (U.K), Vol.<br>25,pp. 162 (1992). |
| 4. | Acharya, Dash and Singh.   | :         | "Magnetic field effects on the free<br>convection and mass transfer flow through porous<br>medium with constant suction and constant heat<br>flux", Indian Jour. Pure Appl. Vol. 31, pp.1 (2000).                             |
| 5. | Noushima Humera, G., Ramana<br>Murthy, M.V.,Rafiuddin and<br>Chennakrishna Reddy, M. | :         | "MHD unsteady free convective walter's<br>memory flow with constant suction and<br>heat sink", Jour. Engg. and Appl. Sci.,<br>Vol. 2, No. 5, pp. 12 (2007).   |
| 6. | Magyari, E., Pop, I. and Keller, B.  | :         | "Analytical solution for unsteady free<br>convection flow through a porous media", Jour.<br>Engg. Math., Vol. 48, pp. 93(2004).   |
| 7. | Soundalgekar, V.M.   | :         | "Unsteady MHD free convection flow  |

past an infinite vertical flat plate with variable suction", Indian Jour. Pure Appl. Math., Vol. 3, pp. 426 (1972).
8. Turchuk, L.I. and Shidlovskil, V.P. : "On the equations of motion of a stratified fluid", Soviet Phys., Doklady, Vol. 25(9), pp. 694 (1980).

9. Mondal, H.K. and Chaudhary, T.K.
 "Unsteady free convective flow of a thermally stratified viscous fluid through a porous medium", Acta Cieneia India, Vol. XIII(2), pp. 101 (1987).