

Review of Design and Analysis of Box Girder Bridges And T-Beam Bridges Using IRC Codes

Shubham Sirse¹, Dr. Kuldeep R. Dabhekar², Dr. Isha P. Khedikar³, M. B. Saiwala⁴

¹M-Tech Scholar, ^{2,3}Assistant Professor, Department of Civil Engineering,

⁴Director, 4D Design Structural Consultants Nagpur, Maharashtra, India

G.H. Raisoni College of Engineering, Nagpur, Maharashtra, India

ABSTRACT

Bridge is the structure which is used for carrying the traffic over the valley or river by connecting highways or railways. There are types of bridges which are T-beam bridges and box girder bridges where the T-beams are effective in resisting bending providing ductility to the bridges. While box girders gives high torsional stiffness providing ductility, stability and also aesthetics. Different codes with varying design philosophy are used for designing these bridges such as IRC:21-2000 and IRC:112-2011. Hence the purpose of this paper is to compare the results of analysis and design of different papers performed using these codes for both the types of bridges i.e. T-beam and box girder bridge. Various researchers studies are available on the design and analysis of T-beam bridge and box girder bridge using IRC:112-2011 and IRC:21-2000. The purpose of this study is to determine the most economical and preferable design code for both T-beam bridges and box girder bridges.

Keywords: IRC: 21-2000, IRC: 112-2011.

I. INTRODUCTION

A formation which is constructed to provide a passing over a gap which may be in the form of valley or river is a called bridge. This may be provided for various purposes which may include passage of water, pedestrians, roadway, and railway. The site for the bridge should have qualities such as equality, effectiveness, efficiency, social and commercial benefits. There is a real importance of bridges in war times; they act as backbones or lifelines for the nation. Bridges has significant importance in humanity and has ideal and aspirational symbol in humans because they are used to connect the people, communities or nation in order to bring them into closer proximity. There are many advantages of bridges such as reduction in the distance, speed in transportation. There is a broad difference in Bridge design all across the world. Different standards from different countries are used design bridges. In India, many

codes are used for bridge such as IRC:21-2000 and IRC:112-2011. These standards are based upon limit state method or working stress method. Now a days, different types of bridge girders are adopted while constructing bridges. There are different types of bridge girders such as T-beam girder and box girder where T-beam bridge decks are one of the most important and preferred type of concrete decks. It is cast in-situ type bridge deck. T-beam bridge decks comprises concrete slab and girders which are connected together monolithically. While box Girder Bridge are also widely used because of their economic and aesthetic solution. In modern highway system, it is used for constructing various structures such as viaducts, grade separation structures, under crossings, over crossings. Box girder has much more torsional rigidity and the closed cellular portion beneath gives pleasing appearance to the bridge as compared to open web type system. IRC had issued two codes in India which are used for designing bridges i.e.

IRC:21-2000 and IRC:112-2011. IRC:21-2000 includes the design philosophy of working stress method and IRC:112-2011 includes the design philosophy of limit state method which have the design provisions for the both Prestress Concrete & RCC Structures. The present paper mainly focus on relative study of different papers analysis and design results carried out using these codes for both the types of bridges i.e. T-beam and box girder bridge. Various researchers studies are available on the design and analysis of T-beam bridge and box girder bridge using IRC:112-2011 and IRC:21-2000. The purpose of this study is to determine the most economical and preferable design code for both T-beam bridges and box girder bridges.

II. LITERATURE REVIEW

Priyanka Dilip P, Fahad P. P. (1), A box girder bridge is an evident bridge section in which main longitudinal girders are provided in the hollow box shape. The box girder are constructed using steel or the concrete after prestressing or they are also constructed in the form of composite or reinforced concrete section. The typical cross section of box girder is rectangular, square and trapezoidal. In this study, 240m span of two Lane Bridge is analysed and designed. A trapezoidal cross-section of post tensioned box girder bridge with two cells is analysed using different design loads using the IRC code for loads and load combinations i.e. IRC:6-2014 which includes different loads such as Super imposed dead load, Dead loads, moving loads, Prestressing force. SAP 2000 is used to analysed the post tensioned box girder bridge using v 19 software. Post tensioning anchorages is carried out by the Freyssinet system.

Phani Kumar, S.V.V.K.Babu, D.Aditya Sai Ram (2), Bridge are used for connecting highway, roadways and railway in the whole world has high level of importance in construction sector. Prestress girder bridges are extremely popular in bridge engineering

field as they are more stable, serviceable, economical and structurally efficient and gives aesthetic appearance. In this thesis, prestressed concrete T-Girder and Box Girder bridges analysis and design are carried out. IRC:112-2011 is used for analyzing the bridges. IRC:112 is a new generation code. The design provisions given in new code differs from previous codes. The previous codes are IRC:18 for prestressed concrete structures and IRC:21 for reinforced concrete structures. IRC:112 based on limit state method and IRC:21 and IRC:18 are based on working stress method which is the main difference between IRC:21 and IRC:112-2011.

Sanket Patel, Umang Parekh (3), The bridges are used for different purposes from the very beginning of human civilization. Innumerable bridges of various kinds and of various materials have been built from times immemorial. Design of medium span highway bridge system requires careful selection of structural element in preliminary stage. The motive behind present study is to prepare some useful interface for preliminary design of bridge system. The most economical design can only be found by comparing few different designs. Particular set of conditions can be used to find the most economic design. Economy can be achieved by separately or simultaneously considering one or more of the following factors: span, superstructure cross section, cost of prestressing steel and concrete consumption. The parametric study of prestressed concrete girder bridge superstructure has been carried out.

Pragya Soni, Dr. P.S. Bokare (4), The bridging activity is as old as human civilization. Innumerable bridges of various kinds and of various materials have been built from times immemorial. Design of medium span highway bridge system requires careful selection of structural element in preliminary stage. The motive behind present study is to prepare some useful interface for preliminary design of bridge system. The

most economical design can only be found by comparing few different designs. Particular set of conditions can be used to find the most economic design. Economy can be achieved by separately or simultaneously considering one or more of the following factors: span, superstructure cross section, cost of prestressing steel and concrete consumption. The present study includes parametric study on prestressed concrete girder bridge superstructure.

Jagdish Chand, Ravikant (5), Sometimes, the way may have barrier or obstacles in the form of river or valley. So, without changing the alignment, a pathway or passage is provided over the barrier or obstacles. Both longitudinal girders and cross girders have been considered in this study of design of bridge girders. Girders are constructed for the individual span of the bridge which is taken as 25m. The size for longitudinal girders and cross girders are taken as 2000x500 mm is 1500x250 mm respectively. The spacing between the three longitudinal girders is taken as 2600 mm c/c and between cross girders as 5000mm c/c. Software STAAD Pro is used to carry out the design of girders. For analysis bridge girder, Three same models are prepared in the STAAD pro and IRC codes, Euro codes and AASHTO loadings are applied. Shear force, bending moment and area of steel is determined from the models according to these different loadings from both longitudinal girder as well as cross girder. The whole analysis is carried out in STAAD Pro and tables and graphs are used to compare the results.

R.Shreedhar, Spurti Mamadapur (6), A simple one span of T-beam bridge was analyzed as a one dimensional structure by using I.R.C. loadings. Software STAAD ProV8i is used to analyse the same T-beam bridge using finite element plate for the beam girder elements for the main beam and deck slab. The one span of bridge is analysed as a three-dimensional structure. Models are analysed for different IRC

loadings .Both the models are treated with I.R.C. Loadings to produce reactions, shear force and maximum bending moment. Manual calculations subjected to IRC loadings are also carried out and are conservative. Lesser results are derived from the finite element model and more results are derived from one dimensional analysis. There are so many types of bridges where T-beam bridge decks are one of the most important and preferred type of concrete decks. It is cast in-situ type bridge deck. T-beam bridge decks comprises concrete slab and girders which are connected together monolithically. In continuum mechanics, solution of a problem is approached by the analysis of collection of finite elements. In this process, finite elements are co-ordinated at nodal points of finite number and this process is used to represents the solution domain of the problem. This is analysed by the finite element method which is generally used for structural analysis.

T. Sujatha ,Y. Yadu Priya (7), Pre-stressed concrete bridges can carry better live loads. In the field of bridge engineering, the use of pre-stressed concrete bridge decks has been expanded in modern days. IRC bridge codes are used to carry out the analysis. The analysis is carried out using IRC provisions. T-beam bridge decks are one of the major and extensively used type of cast in-situ concrete decks. They are consist of a concrete slab integral. T-beam bridge decks are provided with girders. In this method, an equivalent idealized structure is used to replace the actual continuum .STAAD Pro is the general method which is used to analyse the structure. Single span t-beam bridge is analyzed which is a two lane bridge. Different spans are considered where the width is kept constant. The spans which are considered such as 25m, 30m, 35m, 40m. IRC class AA and IRC 70R tracked loading system are used to test the bridge to obtain maximum reactions, maximum bending moment and shear force. From the analysis it is observed that shear force and bending moment in the

girder increases with the increase in the span,. It is also observed that courbon's method and finite element method have no remarkable difference when the results of shear forces and bending moments obtained.

Sharu.E, Nivedhitha M and Gowtham Raja M (8), A bridge is a structure which provides a passage on a valley or an barrier by keeping clear the way beneath. The required passage may be for pedestrians, a road, a railway, a canal or a valley. In the world, many of the bridges are failed due to various reasons. But mostly improper design is the vital reason behind bridge failure. Therefore proper designing is required .R.C.C T-BEAM Bridge in a proper manner. We referred standard code books, standard procedures, and previous research to make a design in a good manner. The span of the bridge which is being of 3 lanes. The clear cover of the reinforcement is taken as 40mm. The bridge is designed with all the components like Deck, Girders, Bearing, Pier cap, Pier, Pile cap, Pile, Abutment and so on and the configuration by IRC loadings. These components are designed based on IRC loadings and it is being examined with the authentic loading. This bridge has also been checked for its seismic resistance capacity. Finally we are bridge with the overloading currently due to congestion factor on the bridge life span of T-beam Bridge.

Prof. R.B. Lokhande ,Abrar Ahmed (9), The development of the nation is mainly from agricultural and industrial activities, so, it is required to facilitate the proper transportation by providing the flyovers and Bridges. T-beam and box type are very popular types of section for constructing the flyovers or the bridges. This project looks on the work of analysis, design and also compares the cost of T-Beam and Box girders for respective spans in order to find out the most suitable section. The purpose of this literature is to determine the most economical and proper section for bridges of respective spans. In this case, the Pre-

stressed concrete sections have been considered. The spans which are designed are more than 25metres.The purpose of this literature is to determine the most economical and proper section for bridges of respective spans. In this case, the Pre-stressed concrete sections have been considered. The spans which are designed are more than 25metres for which it is uneconomical for the Reinforced concrete sections. The objective and aim of the work is to design the sections for different IRC loadings which are given in IRC codes and also analyzing it for those loadings. This has been done by analysing the structure by CSI bridge software and validating with manual results by developing the Microsoft Excel Sheets using Working Stress Method and by adopting Courbon's theory. It is noticed that the IRC 70R vehicle loading creating maximum bending moments and reactions on the sections. Cost comparison of bridge is done and the results has shown that the 30metre spans T-beam girder is suitable, as we go for higher spans the depth of T-beam girder increases drastically which makes it uneconomical Therefore it is concluded that the box girder is suitable for greater spans. The analysis result can be used to find the most suitable and economical section for respective spans of bridge. From the obtained results we can conclude that the software results are reasonable and it can be adopted for the design of substructures.

Sudip Jha, Cherukupally Rajesh, P.Srilakshmi (10), The development of the nation is mainly from agricultural and industrial activities, so, it is required to facilitate the proper transportation by providing the flyovers and Bridges. T-beam and box type are very popular types of section for constructing the flyovers or the bridges. This project looks on the work of analysis, design and also compares the cost of T-Beam and Box girders for respective spans in order to find out the most suitable section. The purpose of this literature is to determine the most economical and proper section for bridges of respective spans. In this case, the Pre-stressed concrete sections have been

considered. The spans which are designed are more than 25metres. The purpose of this literature is to determine the most economical and proper section for bridges of respective spans. In this case, the Prestressed concrete sections have been considered. The spans which are designed are more than 25metres for which it is uneconomical for the Reinforced concrete sections. The objective and aim of the work is to design the sections for different IRC loadings which are given in IRC codes and also analyzing it for those loadings. This has been done by analysing the structure by CSI bridge software and validating with manual results by developing the Microsoft Excel Sheets using Working Stress Method and by adopting Courbon's theory. It is noticed that the IRC 70R vehicle loading creating maximum bending moments and reactions on the sections. Cost comparison of bridge is done and the results has shown that the 30metre spans T-beam girder is suitable, as we go for higher spans the depth of T-beam girder increases drastically which makes it uneconomical Therefore it is concluded that the box girder is suitable for greater spans. The analysis result can be used to find the most suitable and economical section for respective spans of bridge. From the obtained results we can conclude that the software results are reasonable and it can be adopted for the design of substructures.

III. CONCLUSION

The available research paper of design and analysis of box girder and T-girder using IRC:112-2011 and IRC:21-2000 has been studied. It is found that, the bridge girder has been analysed. Hence, after comparing the results from the research papers, the conclusions are made under three points.

- 1. Deflection - It has been found from the literatures that deflection in case of limit state method i.e. IRC:112-2011 is less or within limits than that of IRC:21-2000.
- 2. Quantity of steel – After comparing the steel from both the method, it is found that, there is a considerable difference in steel quantity. IRC:112-2011 (LSM) consumes less steel than IRC:21-2000 (WSM).
- 3. Quantity of concrete- the quantity of concrete can be saved upto 20 to 30% by IRC:112-2011 (LSM).
- From the above points it can be concluded that, IRC:112-2011(LSM) is most economical and preferable design code for T-beam bridges and Box girder bridges.

IV. REFERENCES

- [1] Fahad P. P. , Priyanka Dilip P, “ Analysis and Design of Post Tensioned Box Girder Bridge Using SAP 2000,” IJSRSET , Volume 3 , Issue 2 , Print ISSN: 2395-1990, Online ISSN : 2394-4099,2017.
- [2] Phani Kumar, S.V.V.K.Babu, D.Aditya Sai Ram, “Analysis and Design of Prestressed Box Girder Bridge by IRC: 112-2011,” International Journal of Constructive Research in Civil Engineering (IJCRCE) Volume 2, Issue 2, PP 1-10 ISSN 2454-8693, 2016.
- [3] Sanket Patel, Umang Parekh, “Comparative Study of PSC. Tee Girder and PSC.Box Girder,” IJSTE - International Journal of Science Technology & Engineering , Volume 2 , Issue 11 , May 2016.
- [4] Pragya Soni, Dr. P.S. Bokare, “Review of Design Procedure for Box Girder Bridges,” International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; Volume 5 Issue IX, September 2017.

- [5] Jagdish Chand, Ravikant, "Design and Analysis of Bridge Girders using Different Codes", International Journal of Engineering and Innovative Technology (IJEIT), ISSN: 2278-0181, Vol 8 Issue 07, July-2019.
- [6] R.Shreedhar, Spurti Mamadapur, "Analysis of T-beam Bridge Using Finite Element Method", International Journal of Engineering and Innovative Technology (IJEIT), Issue 3, Volume 2, September 2012.
- [7] T. Sujatha ,Y. Yadu Priya , "Comparative Analysis of Post Tensioned T-Beam Bridge Deck by Rational Method and Finite Element Method," International Journal of Research in IT, Management and Engineering, ISSN 2249-1619, Issue 09, Volume 06, September 2016.
- [8] Sharu.E ,Nivedhitha M and Gowtham Raja M , "design of RCC t-beam bridge considering overloading due to congestion," Indian J.Sci.Res. 17(2): 211 - 216, 2018.
- [9] Prof. R.B. Lokhande ,Abrar Ahmed,"comparative analysis and design of t-beam and box girders," International Research Journal of Engineering and Technology (IRJET) Volume: 04 Issue: 07 , e-ISSN: 2395-0056 | July -2017.
- [10] Sudip Jha, Cherukupally Rajesh, P.Srilakshmi, "Comparative Study of RCC Slab Bridge by Working Stress (IRC: 21-2000) and Limit State (IRC: 112-2011)," Volume No: 2, Issue No: 8 ISSN No: 2348-4845, August 2015.

Cite this article as :

Shubham Sirse, Dr. Kuldeep R. Dabhekar, Dr. Isha P. Khedikar, M. B. Saiwala, "Review of Design and Analysis of Box Girder Bridges And T-Beam Bridges Using IRC Codes", International Journal of Scientific Research in Science and Technology (IJSRST), Online ISSN : 2395-602X, Print ISSN : 2395-6011, Volume 7 Issue 3, pp. 184-189, May-June 2020. Available at doi : <https://doi.org/10.32628/IJSRST207332>
Journal URL : <http://ijsrst.com/IJSRST207332>